



3.5 HDD DATA SHEET

The Power of Agility for Home,
SOHO and SMB NAS enclosures

IronWolf™ is designed for everything NAS. Get used to tough, ready and scalable 24x7 performance that can handle multi-drive environments with a wide range of capacities.



Best-Fit Applications

- 1- to 8-bay network attached storage (NAS)
- Desktop RAID and servers
- Multimedia server storage
- Private cloud

Key Advantages

Optimised for NAS with AgileArray™. AgileArray is built for dual-plane balancing and RAID optimisation in multi-bay environments with the most advanced power management possible.

High performance means no lag times or downtime for users during high traffic time for the NAS. Seagate leads the competition with the highest performance in NAS-class drives.¹

Range of capacities up to 10 TB. More capacity options mean more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

Get ahead with more cache. IronWolf provides high-cache options allowing your NAS to serve data faster.

Do more with multi-user technology. Enables user workload rate of 180 TB/year. Multiple users can confidently upload and download data to the NAS server, knowing it can handle the workload, whether you're a creative professional or small business.

Designed for always on, always accessible 24x7 performance. Access your data on your NAS any time, remotely or on site.

1M hours MTBF, 3-year limited warranty represents an improved total cost of ownership (TCO) with reduced maintenance costs.

¹ Performance may vary depending on user's hardware configuration and operating system.



Specifications	10 TB ¹	8 TB ¹	6 TB ¹	4 TB ¹	3 TB ¹	2 TB ¹	1 TB ¹
Standard Model Numbers	ST10000VN0004	ST8000VN0022 ²	ST6000VN0041 ²	ST4000VN008 ²	ST3000VN007 ²	ST2000VN004 ²	ST1000VN002 ²
Interface	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s
Features and Performance							
Number of Drive Bays Supported	1 to 8	1 to 8	1 to 8	1 to 8	1 to 8	1 to 8	1 to 8
Multi-User Technology (TB/yr)	180	180	180	180	180	180	180
Dual-Plane Balance	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Error Recovery Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Max Sustained Data Rate OD (MB/s)	210	210	195	180	180	180	180
Spindle Speed (RPM)	7,200	7,200	7,200	5,900	5,900	5,900	5,900
Cache (MB)	256	256	128	64	64	64	64
Reliability/Data Integrity							
Load/Unload Cycles ³	600,000	600,000	600,000	600,000	600,000	600,000	600,000
Non-recoverable Read Errors per Bits Read, Max	1 per 10 ¹⁵	1 per 10 ¹⁵	1 per 10 ¹⁵	1 per 10 ¹⁴			
Power-On Hours (per year)	8,760	8,760	8,760	8,760	8,760	8,760	8,760
Workload Rate Limit (WRL) (TB/year)	180	180	180	180	180	180	180
Mean Time Between Failures (MTBF) (hours)	1M	1M	1M	1M	1M	1M	1M
Warranty, Limited (years)	3	3	3	3	3	3	3
Power Management							
Startup Current, Typical (12 V,A)	1.8	2.0	2.0	2.0	2.0	2.0	1.2
Average Operating Power (W)	6.8	9.0	9.0	4.8	5.6	5.0	3.6
Idling Average (W)	4.42	7.2	7.2	3.95	4.9	3.7	2.5
Standby Mode/Sleep Mode, Typical (W)	0.8/0.8	0.6/0.6	0.6/0.6	0.5/0.5	0.6/0.6	0.8/0.8	0.8/0.8
Voltage Tolerance (5 V)	±5%	±5%	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance (12 V)	±10%	±10%	±10%	±10%	±10%	±10%	±10%
Environmental							
Temperature (°C)							
Operating (ambient, min)	5	5	5	5	5	5	5
Operating (drive case, max) ⁴	70	70	70	70	70	70	70
Non-operating (ambient, min)	-40	-40	-40	-40	-40	-40	-40
Non-operating (ambient, max)	70	70	70	70	70	70	70
Halogen-free	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Shock, Operating/Non-operating: 2ms (max, Gs)	70/250	20/250	70/300	80/300	80/300	80/300	80/300
Acoustics							
Idle (typical, bels) ⁵	2.8	2.7	2.7	2.3	2.3	1.9	2.1
Operating (typical, bels)	3.2	2.8	2.8	2.5	2.5	2.1	2.3
Physical							
Height (mm/in, max)	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028	20.17/0.795
Width (mm/in, max)	101.85/4.01	101.6/4.010	101.6/4.010	101.6/4.010	101.6/4.010	101.6/4.010	101.6/4.010
Depth (mm/in, max)	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787
Weight (g/lb, typical)	650/1.433	780/1.72	780/1.72	610/1.345	610/1.345	535/1.18	415/0.915
Carton Unit Quantity	20	20	20	20	20	20	20
Cartons per Pallet / Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8

¹ One terabyte, or TB, equals one trillion bytes when referring to drive capacity.

² Coming in Autumn 2016. For immediate needs, please see Seagate NAS HDD.

³ Load/Unload tested to 600,000 cycles.

⁴ Seagate does not recommend operating at sustained case temperatures above 60°C. Operating at higher temperatures will reduce useful life of the product.

⁵ Idle measured in Idle1 state.

seagate.com



AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2016 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1904.1-1606GB June 2016