



GRAFICKÉ KARTY

GeForce RTX™ 4070 Ti GAMING X TRIO 12G



SPECIFICATIONS

Model Name	GeForce RTX™ 4070 Ti GAMING X TRIO 12G
Cores	7680 Units
Memory	12GB GDDR6X
Standard sběrnice	PCI Express® Gen 4
Rozhraní paměti	192-bit
Takt jádra (MHz)	Extreme Performance: 2760 MHz (MSI Center) Boost: 2745 MHz (GAMING & SILENT Mode)
Takt paměti (MHz)	21 Gbps
Max připojených displejů	4
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
HDCP podpora	Y
Digital Maximum Resolution	7680 x 4320
Doporučený výkon zdroje (W)	700W
Napájecí kabely	16-pin x 1
Podpora DirectX verze	12 Ultimate
Podpora OpenGL verze	4.6
Rozměry (mm)	337 x 140 x 62 mm
Váha (g)	1613 g / 2522 g

CONNECTIONS



FEATURES

TRI FROZR 3



Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



The CNC machined nickel-plated copper base captures heat from the GPU and the memory then rapidly transfers it to Core Pipes.



Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



A die-cast anti-bending plate reinforces the card while thermal pads allow cooling to reach critical component underneath.



Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.