

MG28UQ 4K UHD 1ms Fast Gaming Monitor

Dominate the Digital Battlefield



■ Key Features ■



4 times the resolution of full HD for stunning details and image quality



Quick response time of 1ms (GTG) eliminates ghosting and tracers for game play



To experience true 4K output through HDMI (v2.0)



One-click Visuals Optimization

Exclusive GameVisual function provides 6 preset modes delicately designed for every gaming needs



Play Like a Pro

To select crosshair, timer and FPS counter function for advanced gaming settings



Flicker-free

To eliminate the disturbing flickers on screen to reduce eye fatigue



Ultra-low Blue Light

You could choose from 4 levels of Ultra-low Blue Light modes for your best viewing and users scenario



5-way Navigation

Exclusive 5-way OSD navigation joystick provides a better and ergonomic user experience



4-way Ergonomic Stand

Ergonomically-designed monitor comes with swivel, tilt, pivot, and height adjustments for ideal viewing position.

■ Specification ■

Display	<p>Panel Size : 28"(71.12cm) Wide Screen (16:9) Panel Type :TN Color Saturation : 72% NTSC True Resolution : 3840x2160 @60Hz with DisplayPort1.2/ HDMI (v2.0), 3840x2160 @30Hz with HDMI (v1.4) Pixel Pitch : 0.16mm (157ppi) Brightness(Max) : 300 cd/m² ASUS Smart Contrast Ratio (Max.) : 100,000,000:1 Display Color : 1073.7 M Viewing Angle (CR ≥ 10) : 170°(H)/160°(V) Response Time : 1ms (Gray to Gray) Flicker free</p>
Video Features	<p>Trace Free Technology GameVisual (Scenery, Racing, Cinema, RTS/RPG, FPS, sRGB and User Modes) HDCP support (2.2) Color Temperature Selection(4 modes) Skin Tone Selection (3 modes) GamePlus (Crosshair / Timer/ FPS Counter/Display Alignment) VividPixel Technology Blue Light Filter Adaptive-Sync technology supported (40Hz-60Hz)</p>
Audio Features	<p>2W x 2 Stereo, RMS</p>
Convenient Hotkey	<p>5-way navigation joystick GameVisual Input Selection GamePlus</p>
Input / Output	<p>DisplayPort1.2, HDMI (v2.0), HDMI (v1.4) x2, USB3.0 ports (Upstream x 1, Downstream x 2 / Power charge BC1.2)</p>
Signal Frequency	<p>Digital Signal Frequency : 87~134KHz(H)/ 40~60Hz(V)</p>
Power Consumption	<p>Power Consumption < 62.9W (based on ES 6.0) Power Saving Mode <0.5W Power Off Mode <0.5W</p>
Mechanical Design	<p>Chassis Colors : Black Stand Adjustment : Height: 0~150mm, Tilt : +20°~ -5° , Swivel : +60°~-60° , Pivot : 90°(clockwise), VESA Wall Mounting : 100x100mm Quick Release Stand</p>
Security	<p>Kensington lock</p>
Dimension (WxHxD)	<p>Phys. Dimension with Stand(WxHxD) : 660.26 x (416~566) x233.4 mm Phys. Dimension without Stand (WxHxD) : 660.26 x 380.67x 67.40 mm Box Dimension(WxHxD) : 777 x 467 x 224 mm</p>
Weight	<p>Net Weight (Esti.) : 8.0 kg Gross Weight (Esti.) : 11kg</p>
Accessory	<p>Power cord, DP cable, HDMI Cable, USB 3.0 cable, Warranty card, QSG, Support CD</p>
Compliance and Standards	<p>Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC, BSMI, CU(EAC), RCM(C-Tick), VCCI, J-MOSS, PSE, RoHS, WEEE, Windows 7 / 8.1/10 WHQL, KC,KCC & eStandby , MEPS, TCO6.0, PSB, UkrSEPRO</p>