

SPEAK2 40

Next-generation professional audio in a portable speakerphone

- › Full Duplex audio for natural conversations
- › Voice Level Normalization equalizes all voices
- › Certified for leading virtual meeting platforms
- › Four beamforming noise-cancelling microphones
- › Full-range 50mm speaker & wideband audio
- › IP64-rated protection from dust and water



General info	Box contents	Speakerphone, carry pouch, safety information and warranty
	Packaging dimensions (WxHxD)	142mm x 46.5mm x 139mm 5.6in x 1.8in x 5.5in
	Main unit dimensions (ØxH)	120mm x 33mm 4.72in x 1.3in
	Main unit weight	245g 8.64oz
	IP rating *	IP64-rated protection from dust and water
	Warranty	2 years
	Certifications and compliance	Microsoft Teams (variant dependent), Zoom, Google Meet, Amazon Chime
Audio	Ideal for room sizes	Up to 4.5m x 4.5m 14.76ft x 14.76ft
	Number of microphones	4
	Microphone type	Digital MEMS
	Microphone frequency range	150Hz - 7000Hz
	Microphone pick up range	Up to 2.3m 7.5ft
	Full Duplex	Yes
	Speaker size	50mm 1.97in
	Peak audio output	83 dBspl @ 0.5m
	Speaker bandwidth (music mode)	100Hz - 20000Hz
	Speaker bandwidth (speak mode)	150Hz - 7000Hz
	Acoustic echo cancellation (AEC)	Yes
	Voice Level Normalization (Automatic Gain Control, AGC)	Yes (for outgoing audio)
	Wideband	Up to 8000 Hz
Noise reduction on calls	Yes	
Software & Apps	Compatible software and/or apps	Jabra Direct, Jabra Xpress

Connectivity	Connectivity	USB C or USB A
	Integrated USB cable length	ca. 80cm 31.5in
Extended info	Operating temperature	0°C to 40°C 32°F to 104°F
	Storage temperature	-20°C to 45°C -4°F to 113°F

Products	2740-209	Jabra Speak2 40 - UC, Dark Grey
	TAA2740-109	Jabra Speak2 40 - MS Teams, Dark Grey
Accessories	14208-10	Jabra Kensington Lock Adaptor

* Avoid exposing the USB cable or adapter plug to moisture or liquids and never charge or power up if the USB cable or adapter plug is wet or moist.

Jabra Speak2 40 Tech Sheet 02022023

Download the latest version of this document at:
jabra.com/support