



SONY

CHARGING ACCESSORIES



USB Cables
AC Adapters
Car Charger



**Fast Charge
& Data Transfer**



**High Durability
& Reliability**



Safety



Sony charging accessories are designed with respect to Sony standards.



Fast Charge & Data Transfer



Cables

Wide diameter cable for fast charging

Normal diameter cable



Wide diameter cable



*Charging current may vary based on models, software and charging condition.

Integrated data wire for HI-SPEED data transfer

Regular

No wire for Data transfer



Wire for electric current (GND & Vbus)

SONY



Wire for Data transfer

Up to 480Mbps Data Transfer Speed



AC Adapters / Car Charger

Conventional Adapter	Sony fast charge AC Adapter/ Car charger Approx. 3~6x* faster (Max 1.5A~3A*)			
	CP-AD2M2	CP-AD2	CP-CADM2	CP-AD3
				
0.5A	1.5A	2.1A	2.4A	3.0A
				
	10%	30%	40%	55%
 After 30 minutes of charging				

*Charging speed and current may vary based on smartphone's models, software and charging condition.

High Durability & Reliability



High durability against bent

Due to **wide diameter** and **high quality material**, Sony USB cables **last 2X** longer than other brands cables. This bent durability reduces cable disconnection risk.

For model CP-ABP150 the bend lifespan durability is 10,000+ times.



Bend Lifespan

Sony	3,000+ times
Other	Approx. 1500+ times


Wide diameter and high quality material

High durability against connect/disconnect

Due to **high quality material**, Sony USB cables **last long**. This connect/disconnect durability supports stable operation of both charging & data transfer.



Connect/ disconnect Lifespan
10,000+ times



Connection Lifespan
3,000+ times

With Sony's excellent quality checks, the adapters are carefully engineered to withstand the stress of heavy use over time.

Connection Lifespan
5,000+ times

Safety




USB-IF Official certified cable (USB 2.0)



*USB-IF Official certification does not exist for 3m cable. Due to this reason, CP-AB300 is not USB-IF Official certificated cable but it passed SONY internal test to guarantee safety quality.

Integrated Ferrite core

Except CP-CC100




More stable operations for the surrounding devices.

Cable without Ferrite core



Noise is generated and interferes with other devices

Cable with Ferrite core



Noise is reduced by ferrite core. Does not interfere with other devices

Sony's AC adapters and Car Charger are equipped with **intelligent power controller** that keeps your device safe.



- **Short circuit prevention**
Prevents fire & smoke damage from overheating.



- **Temperature monitoring**
Automatic shut down will be initiated if temperature exceeds the operational limits.
* Except CP-AD2



- **Surge protection**
Prevents your components from overheating during a surge in current.



Sony USB Cable Line Up

Model	CP-AB50	CP-AB150	CP-AB300	CP-ABP150	CP-AC100	CP-CC100	Lightning cable CP- ABLP150
Image							
Color	○	○ ●	●	○ ●	○	○	○ ●
Cable Type	USB A - Micro USB				USB-A to USB-C	USB-C to USB-C	USB A - Micro USB + Micro USB- Lightning adaptor
Length	0,50 m	1,5 m	3,0 m	1,5 m	1,0 m	1,0 m	1,5m
Max Current ^{*1}	2.4A				3.0A		2.4A
Data Transfer Speed	480Mbps						
USB-IF Official certified cable (USB2.0)	-	✓	- ^{*2}	-		✓	-
Bent durability	× 3,000+ times			× 10,000+ times	× 3,000+ times		× 10,000+ times
Connect/ disconnect durability	× 10,000+ times						
Size (φ)	φ4.2 ±0.1mm			φ4.6 ±0.15mm	φ3.9 ±0.1mm		φTBD ±0.15mm
Product Weight	23 g	67 g	121 g	65 g	41 g	40 g	44g
Package Size (inc. hook) W x H x D mm	80 x 181 x 26	80 x 181 x 42	80 x 181 x 51	80 x 181 x 42	80 x 181 x 26	80 x 181 x 26	80 x 181 x 42
Gross Weight (inc. PKG, IM)	62 g (WW)	126 g (WW)	186 g (WW)	124 g (WW)	80 g (WW)	79 g (WW)	-

*1 Charging current may vary based on models, software and charging condition.

*2 USB-IF Official certification does not exist for 3m cable. Due to this reason, CP-AB300 is not USB-IF Official certificated cable but it passed very strict SONY internal test to guarantee product safety.



Sony AC Adapter Line-up

Model	CP-AD2	CP-AD2L	CP-AD2ACWC	CP-AD2M2WC	CP-AD2M4WC	CP-AD3
						
Color	○	○	○	○	○	○
Body	Plastic					
incl. cable	50cm A-B cable (USB2.0)	150cm A-B cable (USB2.0)	150cm A-C cable (USB2.0)	50cm A-B cable (USB2.0)	-	50cm C-C cable (USB2.0)
Input	AC100-240V 0.3A 15W	AC100-240V 0.3A 15W	AC100-240V 0.3 15W	AC100-240V 0.4A 24W	AC100-240V 0.8A 43W	AC100-240V 0.4A 24W
Hz	50/60Hz					
Output	DC5V 2.1A	DC5V 2.1A	DC5V 2.1A	DC5V 3A	DC5V 6A(2.4Ax1, 1.5Ax3)	DC5V 3A
port	1	1	1	2	4	1
Size (W x H x D mm)	41.0 x 61.0 x 44.5	41.0 x 61.0 x 44.5	44.0 x 26.0 x 75.5	44.0 x 26.0 x 75.5	60.5x78.2 x31.0	44.0 x 26.0 x 75.5
Weight(g)	61	61	61	69	133	68
Package Size (inc. hook) W x H x D mm	102 x 170 x 71	102 x 170 x 71	112 x 181 x 34	102 x 171 x 34	127 x 172 x 35	102 x 171 x 34
Gross Weight (inc. PKG, IM, Cable)	218g	172g	185g	149g	243g	148g
Plug	Direct	Direct	Direct	Direct	Power cord (0.5m)	Direct
Over charge current protection	✓	✓	✓	✓	✓	✓
Short Circuit protection	✓	✓	✓	✓	✓	✓
Temperature Monitoring	✓	✓	✓	✓	✓	✓



Car Charger Line-up

Model	CP-CADM2
	
Color	●
incl. cable	-
Input	DC12/24V 3.0A
Output	DC5V 4.8A(2.4AX2)
port	2
Size (W x H x D mm)	28.4 x 68.6 x 28.4
Weight (g)	24
Package Size (inc. hook) W x H x D mm	70 x 156 x 33
Gross Weight (inc. PKG, IM, Cable)	66 g
Plug	Direct from car lighter socket
Over charge current protection	✓
Short Circuit protection	✓
Temperature Monitoring	✓
LED indicator(single)	✓

For Office



For Home



For Travel



For Car



SONY

Sony and the Sony logo are trademarks of Sony Corporation.
USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum, Inc.