



# Industrial printers designed for high-volume label printing

TJ-4420TN / TJ-4520TN / TJ-4422TN / TJ-4522TN Data Sheet

## Performance you can rely on

Designed for high-volume label printing, the Brother TJ series is capable of printing more than a thousand labels a day.

The durable label printers offer rapid print speeds, large ribbon capacity and an internal rewinder on selected models - making them perfect for any industrial printing application.

### Key Features:

- Various printer command languages supported, including ZPL2 emulation
- Rapid print speeds up to 14ips (356 mm/sec)
- Automatic internal rewinder on selected models
- High capacity 600m ribbon to minimize downtime
- In-built durability for tough production environments
- LCD and touch panel displays available for a first-class user experience
- Flexible connectivity options with USB, USB Host, Serial, Ethernet and optional Wireless and Bluetooth (single module)



## General

<b>Carton contents</b>	Power cord USB cable Documentation
<b>Language support</b>	Dansk, Deutsch, English, Español, Français, Italian, Nederlands, Norsk, Português, Suomi, Svenska

## Dimensions & Weights

<b>Without carton</b>	<b>TJ-4420TN   TJ-4520TN:</b> 276mm (W) x 502mm (D) x 326mm (H) 15.35kg
	<b>TJ-4422TN   TJ-4522TN:</b> 276mm (W) x 502mm (D) x 412mm (H) 18.93kg

## Built In Features

<b>Printing Method</b>	Direct Thermal / Thermal Transfer
<b>Print Resolution</b>	<b>TJ-4420TN   TJ-4422TN:</b> 203dpi <b>TJ-4520TN   TJ-4522TN:</b> 300dpi
<b>Maximum print speed</b>	<b>TJ-4420TN   TJ-4422TN:</b> 356 mm/sec <b>TJ-4520TN   TJ-4522TN:</b> 305 mm/sec
<b>Maximum print width</b>	104mm
<b>Minimum print length</b>	Continuous: 5mm Tear mode: 50 mm** Peeler mode: 12.7mm** Cutter mode: 25.4mm**
<b>Maximum print length</b>	<b>TJ-4420TN   TJ-4422TN:</b> 25400mm <b>TJ-4520TN   TJ-4522TN:</b> 11430mm
<b>Minimum media width</b>	20mm
<b>Maximum media width</b>	114mm
<b>Maximum roll diameter</b>	203mm
<b>Minimum roll core diameter</b>	38.1mm
<b>Maximum roll core diameter</b>	76.2mm
<b>Minimum ribbon width</b>	25.4mm
<b>Maximum ribbon width</b>	114.3mm
<b>Inner paper core &amp; ribbon length</b>	1" paper core: Max. OD 90mm, 600m long
<b>Interfaces</b>	USB Ver.2.0 (Full Speed) (Type B), USB Host Serial RS232C (DB9 female) Wired LAN 10/100BASE-TX Wi-Fi 802.11 a/b/g/n & Bluetooth v4.2 (single-module option)

<b>Control Panel</b>	<b>TJ-4420TN   TJ-4520TN:</b> LCD display, 1 status indicator and 6 button navigation  <b>TJ-4422TN   TJ-4522TN:</b> Colour touch display, 1 status indicator and 6 button navigation
<b>Printer commands</b>	FBPL-EZD (EPL2,ZPL2,DPL)
<b>Internal fonts &amp; sizes</b>	8 alpha-numeric bitmap fonts for FBPL Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
<b>Memory</b>	RAM: 256MB Flash: 512MB (MicroSD Flash memory card reader or Flash memory expansion up to 32 GB)
<b>Internal Barcode</b>	<b>Linear:</b> Code128UCC, Code128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Standard 2 of 5, Industrial 2 of 5, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, EAN14, Code11, TELEPEN, TELEPEN number, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS  <b>2-dimensional:</b> CODABLOCK F mode, GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF417, TLC39
<b>Operating system support</b>	Microsoft® Windows® 7 / 8.1 / 10 / Server 2012 / Server 2012R2 / Server 2016 / Server 2019  OS X 10.11.x macOS 10.12.x,10.13.x,10.14.x 10.15  Ubuntu V11.04-16.04 / Fedora 24 / SUSE Linux Enterprise Server 12 / CentOS Linux 7.2 / Red Hat Enterprise 7.3
<b>Windows SDK</b>	Microsoft® Windows® 7 / 8.1 / 10 Microsoft® Windows® Server 2012 / Server 2012R2 / Server 2016 / Server 2019
<b>Mobile SDK</b>	Android v5 – v10 iOS v9 – v13.2 Requires 3rd party app development using Brother SDK, further information available at <a href="http://www.brother.co.jp/eng/dev/">www.brother.co.jp/eng/dev/</a>
<b>Software</b>	<b>BarTender Ultra Lite Edition:</b> Barcode label design software (download)  <b>Brother Printer Management Tool:</b> Software to centrally manage devices for updating settings, firmware and other configurations. (Microsoft® Windows® 8.1 / Windows® 10 only), Microsoft® Windows® Server 2012 / Server 2016 / Server 2019)

## Environmental

<b>Operating Temperature</b>	0°C to 40°C
<b>Operating Humidity</b>	25% to 85% non-condensing
<b>Storage Temperature</b>	-40°C to 60° C
<b>Storage Humidity</b>	10% to 90% non-condensing

## Supplies

<b>Roll type*</b>	<b>Uncoated label:</b> BUS-1J074102-203: 102mm x 74mm, 2,940 labels BUS-1J150102-203: 102mm x 150mm, 1,500 labels
	<b>Coated label:</b> BCS-1J074102-203: 102mm x 74mm, 2,900 labels BCS-1J150102-203: 102mm x 150mm, 1,440 labels
	<b>Standard Wax:</b> BWS-1D600-110: 110mm x 600m
<b>Ribbon type*</b>	<b>Premium Wax:</b> BWP-1D600-110: 110mm x 600m
	<b>Standard Wax/Resin:</b> BSS-1D600-110: 110mm x 600m
	<b>Premium Wax/Resin:</b> BSP-1D600-110: 110mm x 600m
	<b>Standard Resin:</b> BRS-1D600-110: 110mm x 600m
	<b>Premium Resin:</b> BRP-1D600-110: 110mm x 600m

## Optional Accessories (Dealer Option)

<b>Label Peeler**</b> (with liner rewinder)	PA-LP-006
<b>Cutter**</b>	PA-CU-005
<b>WiFi and Bluetooth Interface (module)</b> (User Option)	PA-WB-001

\*For additional supplies information, please contact your local Brother office

\*\*TJ-4420TN & TJ-4520TN only

\*\*\*TJ-4422TN & TJ-4522TN only

*All specifications are correct at the time of printing and are subject to change without notice. Brother and the brother logo are both trademarks of Brother Industries, Ltd., registered in Japan and certain other countries.*

*Any trade names, logos and product names of other companies appearing are trade names or trademarks of those respective companies.*

*BIE Product Planning: Last updated 30/10/2020*