




# AC1200 Wireless MU-MIMO Gigabit Router

Upgrade to Fast AC Wi-Fi and  
gigabit connections

Archer C6



300Mbps + 867Mbps  
Dual Band Wi-Fi



Gigabit  
Ports




Access Point  
Mode

# Highlights


## Household Wi-Fi at Streaming Speeds

Press play and forget about buffering with the Archer C6. Thanks to high-speed dual Wi-Fi bands, you can run more of your devices at the same time without interruption. The strong 2.4GHz (300Mbps) Wi-Fi band is perfect for sending emails, browsing the web, and listening to music. The crystal 5GHz Wi-Fi band reaches 867Mbps so you can game online and stream in HD simultaneously.



## Beamforming for Better Coverage


Beamforming technology detects the location of your connected devices and concentrates the Archer C6's Wi-Fi towards them to create stronger overall connections.



# Highlights


## MU-MIMO for 2x Faster Connections

MU-MIMO technology simultaneously transfers data to multiple devices at once, reducing wait time, increasing Wi-Fi throughput for every device and making each stream more efficient.




## Optimum Wired Versatility

The Archer C6's multiple Gigabit LAN ports provide your PCs, game consoles and more with ultra-fast and stable wired networks.





# Features



## Ease of Use

- Intuitive Web UI – Ensure quick and simple installation without hassle
- Hassle-free Management with Tether App – Let you easily manage your network settings with your smartphone
- Fast Encryption – Quickly connect devices to Wi-Fi at the push of a button without entering the password
- Access Point Mode – Switch to access point mode to connect Wi-Fi devices to any wired network



## Reliability

- Ultimate Wireless Speed – 300Mbps Wi-Fi speed on 2.4GHz and 867Mbps Wi-Fi speed on 5GHz meet your daily internet needs
- MU-MIMO – Simultaneously transfer data to multiple devices for 2× faster
- Support 802.11 ac – Provide a data transfer rate 3 times faster than 802.11n for each stream
- IPTV – Support IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming



## Security

- Active Defense – Protect your home network with firewalls and wireless encryption
- Guest Network – Provide separate access for guests while securing the home network
- Access Control – Establish a whitelist or blacklist to allow or block certain devices from accessing the internet
- Parental Controls – Manage when and how connected devices can access the internet
- Encryptions for Secure Network – WPA-PSK and WPA2-PSK encryptions provide active protection against security threats

# Specifications

## Hardware

- Ethernet Ports: 4\*10/100/1000Mbps LAN Ports, 1\*10/100/1000Mbps WAN Port
- Buttons: Reset Button, Power On/Off Button, WPS/Wi-Fi On/Off Button
- Antennas: 4 Fixed Omni Directional Antennas
- External Power Supply: 12V/1A
- Dimensions (W x D x H): 9.1 × 5.7 × 1.4 in (230 × 144 × 35 mm)

## Software

- WAN Type: Dynamic IP, Static IP, PPPoE, PPTP (Dual Access), L2TP (Dual Access), BigPond
- DHCP: Server, DHCP Client List, Address Reservation
- Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
- Dynamic DNS: DynDns, NO-IP
- Access Control: Parental Controls, Local Management Control, Host List, White List, Black List
- Firewall Security: DoS, SPI Firewall, IP and MAC Address Binding
- Protocols: IPv4, IPv6
- Management: Access Control, Local Management, Remote Management
- Guest Network: 2.4GHz guest network, 5GHz guest network

## Wireless

- Wireless Standards: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz
- Frequency: 2.4GHz and 5GHz
- Signal Rate:
  - 5GHz: Up to 867Mbps
  - 2.4GHz: Up to 300Mbps
- Transmit Power:
  - CE EIRP: <20dBm(2.4GHz); <23dBm(5GHz)
- Reception Sensitivity:
  - 5GHz:
    - 11a 6Mbps:-93dBm; 11a 54Mbps:-78dBm;
    - 11ac HT20 mcs8:69dBm;11ac HT40 mcs9:-65dBm;
    - 11ac HT80 mcs9:-62dBm;
  - 2.4GHz:
    - 11g 54Mbps:-78dBm;
    - 11n HT20 mcs7:-74dBm;
    - 11n HT40 mcs7:-71dbm;
- Wireless Function: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
- Wireless Security: 64/128-bit WEP,WPA / WPA2,WPA-PSK/ WPA2-PSK encryption

# Specifications

## Others

### · Package Contents

Wireless Router Archer C6  
Power Adapter  
RJ45 Ethernet Cable  
Quick Installation Guide

### · Certification

CE, RoHS

### · Environment

Operating Temperature: 0°C~40°C (32°F ~104°F)  
Storage Temperature: -40°C~70°C (-40°F ~158°F)  
Operating Humidity: 10%~90% non-condensing  
Storage Humidity: 5%~90% non-condensing

### · System Requirements

Microsoft Windows 10/8.1/8/7/Vista/XP/2000/NT/98SE, MAC OS, NetWare, UNIX or Linux  
Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser  
Cable or DSL Modem  
Subscription with an internet service provider (for internet access)

### · Download TP-Link Tether App



For more information, please visit  
<http://www.tp-link.com/en/products/details/Archer-C6.html>  
or scan the QR code left

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-Link Technologies Co., Ltd. Copyright ©2018 TP-Link Technologies Co., Ltd. All rights reserved.

[www.tp-link.com](http://www.tp-link.com)

TP-Link AC1200 Wireless MU-MIMO Gigabit Router Archer C6