NETGEAR®

SOHO Ethernet Switches

Data Sheet

600 Series



Features

- Fast Ethernet switches link multiple devices with a fast auto-switching Ethernet connection
- Gigabit Ethernet switches connect multiple devices, delivering speeds up to 10x faster than Fast Ethernet[†]
- Plug-and-play technology
- · Single color LEDs monitor link and activity
- Supports Fast and Gigabit Ethernet devices with automatic speed-sensing and AutoUplink™ technology
- Supports Windows® and Macintosh® platforms

Wrap-around Mirror Finish

With its distinctive reflective surface, the GS605
 & GS608 blend seamlessly into any environment




Ideal for Small Office & Home Networks

- Instant Internet connectivity
- · Stylish design
- · Reliable performance
- Wall mountable

NETGEAR Green

- Auto power-down mode saves energy when port is unused
- Auto Green mode detects cable length and adjusts power usage to save energy
- Packaging manufactured with at least 80% recycled materials



NETGEAR®

SOHO Gigabit Ethernet Switches

Data Sheet

600 Series

FEATURES	FS605	FS608	GS605	GS608
10/100/1000Mbps PORTS	5	8	5	8
ENCLOSURE	Plastic	Plastic	Plastic	Plastic
PERFORMANCE: Bandwidth Buffer Memory Jumbo Frames	1Gbps 384Kbits 2048 bytes	1.6Gbps 768Kbits 2048 bytes	10Gbps 1Mbit 9216 bytes	16Gbps 1Mbit 9216 bytes
ENERGY EFFICIENCY: Auto Power Down Short Cable Detection DC Input Power Consumption (Max and Standby) On/Off Switch Heat Dissipation (Max and Standby)	● 5V/0.7A 1.8W/0.7W 6.14 BTU/2.39 BTU	► 5V/0.7A 2.3W/1.2W 7.85 BTU/4.10 BTU	5V/0.7A 2.34W/0.45W 7.99 BTU/1.53 BTU	12V/0.5A 3.52W/0.57W • 12.01 BTU/1.95 BTU
ENERGY EFFICIENT ETHERNET (IEEE 802.3az)			•	•
PORT LEDS	•	•	•	•
ADDRESS TABLE SIZE	2K	2K	2K	8K
PHYSICAL SPECIFICATIONS: Width x Depth x Height Weight	118 x 72 x 30 mm 0.09 kg	165 x 94 x 30 mm 0.15 kg	118 x 72 x 30 mm 0.1 kg	158 x 102 x 26 mm 0.2 kg
ENVIRONMENT: Operating Temperature Storage Temperature Operating Humidity Storage Humidity	0 ~ 40° C -20 ~ 70° C 90% maximum relative humidity, non-condensing 10% to 95% relative humidity			

WARRANTY

- China: NETGEAR 1-year warranty
- U.S., Canada & rest of world: NETGEAR 2-year warranty

STANDARDS

- IEEE 802.3i 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet[†]
- IEEE 802.3az Energy Efficient Ethernet
- · Honors IEEE 802.1p and DSCP priority tags
- · Jumbo Frame Support (up to 9216 bytes)



This product comes with a limited warranty that is valid only if purchased from a NETGEAR authorized reseller.

*24/7 basic technical phone support provided for 90 days from purchase date when purchased from a NETGEAR authorized reseller.

†Applies to models GS605, and GS608 only.

Actual SKU availability may vary per region. Please check the local website for latest update.

NETGEAR, the NETGEAR logo are trademarks and/or registered trademarks of NETGEAR, Inc. and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice.

© 2014 NETGEAR, Inc. All rights reserved.