

UISP Switch Pro



Mechanical

Dimensions	442.4 x 267.5 x 43.7 mm (17.4 x 10.5 x 1.7")
Weight	4 kg (8.8 lb)
Enclosure materials	SGCC steel, polycarbonate/acrylonitrile butadiene styrene

Hardware

Total non-blocking throughput	64 Gbps
Switching capacity	128 Gbps
Forwarding rate	95.23 Mpps
Networking interface	(24) GbE RJ45 LAN ports (4) 1/10G SFP+ ports
Management interface	Ethernet In-Band Bluetooth
Power method	(1) Universal AC input, 100–240V AC, 4.4A Max., 50/60 Hz (1) Power TransPort DC input 27V DC, 9.3A
Power supply	AC/DC, Internal, 250W
Supported voltage range	100–240V AC
Max. power consumption	30W (ExcludING PoE output)
ESD/EMP protection	Air: ± 15 kV, contact: ± 8 kV
LCM display	(1) 1.3" touchscreen
Operating temperature	-10 to 50° C (14 to 122° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

PoE

PoE interface	(16) 27V passive PoE: 2-pair (Pins 4, 5+/7, 8-) or 4-pair (Pins 1, 2, 4, 5+/3, 6, 7, 8-); Ports 1 to 16
Total available PoE	220W
Max. passive PoE wattage per port	30W/27V DC
Passive PoE voltage range	27V DC

LEDs

RJ45 data ports	PoE Speed/link/activity
SFP+ data ports	Speed/link/activity

