



## QSW-1108-8T

Management Type	Unmanaged
Number of Ports	8
2.5GbE (RJ45)	8
Power Supply Description	Adapter
Max. Power Consumption	18W
Input Power Type	DC
Input Voltage Range	12V/1.5A
MAC Address Table	16K
Total Non-Blocking Throughput	20Gbps
Switching Capacity	40Gbps
Energy Efficient Ethernet (IEEE 802.3az complaint)	Yes
Fanless	Yes
Supported Standards	IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3bz 2.5GBase-T IEEE 802.3x Full-Duplex Flow Control
Form Factor	Desktop
LED Indicators	Per Port: Speed/Link/Activity Loop LED: Loop Per System: Power/Status
Dimensions (HxWxD)	27 x 240 x 105 mm
Weight (Net)	639 kg
Weight (Gross)	990 kg
Operating Temperature	0°C to 40°C (32°F to 104°F)

Relative Humidity	5~90% Non-condensing
Certifications	FCC, CE, BSMI, VCCI, LVD,CCC,KCC, UKCA
Electromagnetic Compliance	Class B
Jumbo Frames	12K
Warranty	2 Years

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.