ThinkCentre Tiny-In-One 24 Gen 4 11GDPAT1EU

Product

ThinkCentre TIO24Gen4

Region

RUCIS

Machine Type

11GD

Color

Black

Display Size

23.8"

Touchscreen

None

Resolution

1920x1080

Aspect Ratio

16:9

Pixel Pitch

0.2745 mm

Dot / Pixel Per Inch

92.6 dpi

Brightness

250 nits

Contrast Ratio

1000:1

Pixel Response Time

4-14 ms

Color Gamut

72%

View Angle (H / V)

178 / 178

Stand

Adjustable Stand

Camera

1080p

Power Comsuption (Typical / Maximum)

15W / 27W

Power Supply

90W 88% Adapter

Base Warranty

3-year

Ann Date (mm/yy)

05/20

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.

© Lenovo, 2020. All rights reserved.





ThinkContro Tiny In One 24 Con 4 Pletform Specifications

Security keyhole for attachment of optional cable lock (Kensington® lock compatible), locks optional Tiny with TIO together, more security features offered by Tiny installed (optional)

TIO with stand

21.25 x 9.07 x 17.59 - 23.5

539.8 x 230.4 x 446.9 - 596.9

12.92 lb /6.66 kg

TIO without stand

21.25 x 2.57 x 14.47

539.8 x 65.3 x 367.6

7.96 lb /3.61 kg

Dimensions W x D x H (inch)

W x D x H (mm)

Weight (Approx.)

Security

Mechanical

ThinkCentre Tiny-In-One 24 Gen 4 Platform Specifications						
Form factor Compatible Tiny:	Tiny-in-One, offers a full All-In-One experience when optional Tiny slots into the back of TIO, clean cabling and effortless setup P340 / P330 / P320 / M90q / M80q / M70q / M75q / M920(x) / M720 / M910(x) / M710 / M715 / M900(x) / M700 / M630e / M625 / M600 Tiny M90n / M75n Nano (with TIO kit)	Mounting features Adjustable stand	Wall or desk mounting using the extermeeting the VESA FPMPMI® (100mm Tilt: 30° back, -5° forward; lift: 5.9" (150mm); swivel: +/-45°; Pivot: clockwise -5° to 90°		y accessories	
Panel Viewable image size	TFT-LCD, In-Plane Switching technology**, White LED backlight Notes: In-Plane Switching may refer to IPS, PLS, ADS, AHVA, AAS panels 23.8" (604.7mm) diagonal 20.75" x 11.67" / 527.0mm x 296.5mm Top / Side: 2mm, Bottom: 22.1mm 1920x1080 @60Hz 25 Optional 10-point multi-touch, AIT technology 16:9 0.2745mm	Power supply Power consumption	90 watts AC/DC adapter, 88% PSU, universal 27 watts max, 15 watts typical, <0.5 watts standby / suspend			
Max view area (W x H)		Limited warranty	3-years, Carry-In or Courier service	3-years, Carry-In or Courier service		
Native resolution Presets / user settings Multi-touch Aspect ratio 1920x1 25 Optiona 16:9		Environmental Windows certifications	TCO 8.0, TCO edge 2.0, ENERGY STAR® 8.0, EPEAT™ Silver rating, UL GREENGUARD Certified, Erp lot5, WEEE, RoHS, TUV Eye comfort Windows 7 and Windows 10 certified			
		Ship group	TIO (Monitor), detachable stand, power adapter, power cord, information flyer, user's guide, and driver CD			
Dot/Pixel per Inch	92.6 dpi	Accessories	For compatible accessories, please g	For compatible accessories, please go to http://smartfind.lenovo.com		
Brightness Contrast ratio	250 nits or cd/m² (typical) 1000:1 (typical)					
Pixel response time Color gamut	14ms (default), over drive to 4ms, 6ms 72% NTSC (CIE 1931)		ThinkCentre Tiny-In-One 24 Gen 4 Compatible list			
Anti-reflective	Anti-glare `	Model	P340 / P330 / P320	M93/p / M83 /	Chromebox	
	R178° (+/- 89°) horizontal, 178° (+/- 89°) vertical		M90q / M80q / M70q / M75q / M920(x) /	M73 / M53 Tiny		
On screen display Control features	On screen display with digital user controls (8 languages) Ftont: Exit button, Up / Mode-switching button (TIO / monitor mode, switchs the sources of both display and side USB port),		M720 / M910(x) / M710 / M715 / M900(x) / M700 / M630e / M625 / M600 Tiny M90n / M75n (with TIO kit)			
TIO Power On features	Down / Brightness button, Enter / Menu button, Power button Bottom: Volume up button, Volume down button Pressing Alt + P (on keyboard) or Power button (on TIO) can turn on both TIO and Tiny (Some old Tiny cannot fully support, see compatible list)	Turn on TIO and Tiny together via Alt + P on USB KB	All models	All models	Not support	
Side ports (on TIO)	One USB Type A port (The availability and version depends on the Tiny istalled or the PC connected via USB upstream port)	Turn on TIO and Tiny together via	All models	Not support	All models	
Side ports (on Tiny)	Side ports offered by installed Tiny (front ports)	TIO Power Button				
Rear ports 3-in-1 Cable	One DisplayPort in port, one USB upstream port, one power connector Undetachable 3-in-1 cable (Power connecter, USB [supports USB 3.1 Gen1 / USB 2.0], DisplayPort), only for connecting to Tiny installed (optional)			·		
Camera	Some: 1080p camera with dual microphone and Think Shutter Some: RGBIR camera with dual microphone, support Think Shutter					
Internal Speaker	2 watt x2					















