Lenovo

ThinkCentre M75q Tiny 11A4000HXS

Product

ThinkCentre M75q-1 Tiny

Region

EET

Country/Region

Slovakia

Machine Type

11A4

TopSeller

TopSeller

Processor

AMD Ryzen 5 PRO 3400GE (4C / 8T, 3.3 / 4.0GHz, 2MB L2 / 4MB L3)

Chipset

AMD B300 Chipset

Graphics

Integrated AMD Radeon Vega 11 Graphics

Memory

1x 8GB DDR4-2666

Storage

256GB SSD M.2 2280 PCIe x4 NVMe opal

Optical

None

Speaker

1.5Wx1

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

RTL8822CE 11ac. 2x2 + BT5.0

Optional Rear Ports

1x DP

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

Adapter Cage

Toolless Chassis Screw

Toolless Chassis Screw

Dust Filter

None

VESA Mount

VESA Mount

Wireless Charger

Color

Black

Stand

None

Keyboard

USB Traditional Keyboard, Slovak

Mouse

USB Calliope Mouse

Power Supply

65W 88% Adapter

TUV Low Noise

None

Monitor Cable

None

System Management

DASH

Operating System

Windows 10 Pro 64, Slovak / English

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

EAN/UPC

0194552485313

End of Support

2025-11-15

Announce Date

2019-10-15

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2020. All rights reserved.



ThinkCentre M75q-1 Tiny Platform Specifications

Processor	AMD Athlon PRO or Ryzen 3 / 5 PRO series processor						Security features	Security slot (in rear for optional Hard disk password
	Processor	Cores / Threads	Frequency Base/Max	L2 / L3 Cache	Memory Support (Up to)	Integrated Graphics		 Kensington® MicroSaver® cable) Smart USB protection, allows keyboard/mouse only, blocks all storage devices Power-on password Administrator password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch
	Athlon PRO 200GE	2/4	3.2 GHz	1 MB / 4MB	DDR4-2666	Radeon Vega 3		
	Athlon PRO 300GE	2/4	3.4 GHz	1 MB / 4MB	DDR4-2666	Radeon Vega 3		
	Ryzen 3 PRO 2200GE	4/4	3.2 / 3.6 GHz		DDR4-2933	Radeon Vega 8	Keyboard Mouse	Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black (only available via special bid models)
	Ryzen 5 PRO 2400GE		3.2 / 3.8 GHz		DDR4-2933	Radeon Vega 11		
	Ryzen 3 PRO 3200GE		3.3 / 3.8 GHz		DDR4-2933	Radeon Vega 8		
	Ryzen 5 PRO 3400GE	4/8	3.3 / 4.0 GHz	2 MB / 4MB	DDR4-2933	Radeon Vega 11		
Memory	32GB max, DDR4-2666*, two 260-pin SO-DIMM sockets, dual-channel capable * System automatically clocks down for the lower memory controller						Mechanical	Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case
Disk	Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: M.2 SSD (2242 / 2280) / PCIe NVMe, PCIe 3.0 x2 or PCIe 3.0 x4 Some: DVD-ROM, 9.0mm high, via USB external ODD box Some: DVD±RW, 9.0mm high, via USB external ODD box					Cle 3.0 x4		 Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter M75q Tiny only: 7.05" W X 7.20" D X 1.36" H
Optical								
Onboard SATA	One SATA 6.0Gb/s connector on system board							179mm W X 182.9mm D X 34.5mm H
·	AMD Radeon™ Graphics in processor, uses main memory, DirectX® 12, one DisplayPort™, one HDMI, one optional port (VGA, 2nd DP, or 2nd HDMI), supports 3 independent displays (supports maximum of 2 concurrent HDMI/DVI displays when using HDMI port or DP to DVI/HDMI dongles, and Athlon / Athlon PRO only support 2 displays); Max resolution: 4096x2160 (DP)@60Hz; 4096x2160 (HDMI)@30Hz; 1920x1200 (VGA)@60Hz					d HDMI), supports MI/DVI displays Athlon PRO only		2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Monitor cable							VESA mount Optional VESA mount bracket kit, supports VESA 75mm and 100mm Floor Stand Optional system floor stand for vertical orientation	
	Tibivii 1.4 doligie						Power supply	Some: 65 watts adapter, autosensing, 88% PSU (not included for TIO models) Some: 135 watts adapter, autosensing, 88% PSU (not included for TIO models)
	AMD B300 Chipset						Limited warranty	1-year or 3-year, limited onsite service / service upgrades available
Rear ports* (Std.) Rear ports* (Opt.)	tts* (Std.) one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm) ts* (Std.) 1x USB 3.1 Gen1, 3x USB 2.0, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDMI ts* (Opt.) Two optional ports: Port 1 for VGA / 2nd DP / 2nd HDMI / serial; Port 2 for serial; * Depending on many factors, actual data transfer speed may be lower than theoretical speed						Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Some: Windows 10 IoT Enterprise Some: Linux Ubuntu
Audio support WLAN	Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9260 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: Bluetooth 4.2 / 5.0 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Realtek RTL8111EPV-CG, Wake on LAN®					,	Environment	ENERGY STAR® 7.1*, EPEAT™ Silver rating* (*Not for non-OS models);
v v L/-(V						A (dual band),	MIL-SPEC test	ErP Lot 3; RoHS-compliant; TUV low noise verified MIL-STD-810H military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock Fungus, Solar Radiation)
						,,	Accessories	For compatible accessories, please go to http://smartfind.lenovo.com
	DASH 1.0/1.1 Discrete TPM 2.0, TCG Certified							











